MODEL: BV-101 [One Piece Body Ball Valve Reduced Port]

Connection: Screw BSP, NPT




♦ SPECIFICATION

- For chemical and industrial application
- Blow-out proof stem design
- 100% air tested under water at 80-100 psi
- Working pressure : 1000 PSI
- Temperature range -50°C to 220°C

♦ OPTION

- Locking device
- Oval handle
- Butterfly handle

♦ PRESSURE / TEMPERATURE




- PTFE - RPTFE (PTFE+15% Glass)

◆ DIMENSIONS (mm)

SIZE	В	Н	D	L	S	K	W (kg)
1/4"	5	38	62.5	39	17	19	0.07
3/8"	7	40	73	44	21	21	0.11
1/2"	9.2	51	85	56.5	25	27.5	0.18
3/4"	12.5	53	87	59	32	30	0.26
1"	16.0	56	107	71	38	36	0.42
1 1/4"	20	61	107	78	49	40	0.75
1 1/2"	25	68	130	83	53	42.5	0.85
2*	32	73	130	100	65	51	1.35



VTV Valve: 1-piece ball valve is designed for most of the industrial pipe line. On this economic type, the valve become the very basic one in most industrial works.



♦ MATERIAL LIST

ITEM	PART NAME	MATERIALS		
1	INSERT	CF8M		
2	BODY	CF8M		
3	SEAT	PTFE		
4	BALL	SS 316		
5	STEM	SS 316		
6	THRUST WASHER	PTFE		
7	STEM PACKING	PTFE		
8	GLAND WASHER	SS 304		
9	HANDLE	SS 304		
10	WASHER	SS 304		
11	NUT STOPPER	22 304		
12	SLEEVE	PLASTIC		

Specification is subject to change without prior notice

22