


MODEL : DD-205 [Double Door Check Valve]

Connection : Wafer JIS 10K, ANSI 150, PN 16



VTV VALVE, serving Multi-National end users in a wide range of applications in many industries including:


1. Palm Oil and Refinery Plant
2. Food Industries
3. Petrochemical Plant
4. Cooling System




- ◆ Suitable for :
1. Water
 2. Oil
 3. Gases

◆ MATERIAL LIST

NO	PART NAME	MATERIAL				
		A126B	WCB	CF8	CF8M	CF3M
1	Body	A126B	WCB	CF8	CF8M	CF3M
2	Pates	CF8	CF8	CF8	CF8M	CF3M
3	Hinge Pin	SS304	SUS304	SUS304	SUS316	SUS316L
4	Seat	Viton	Viton	Viton	Viton	Viton
5	Spring	SS304	SUS304	SUS304	SUS316	SUS316
6	Washer	SS304	SUS304	SUS304	SUS316	SUS316



*Optional: Metal to metal seated



◆ DIMENSIONS (mm)

MARK	SIZE																		
	2"	2-1/2"	3"	4"	5"	6"	8"	10"	12"	14"	16"	18"	20"	24"	26"	28"	30"	32"	36"
A	103	123	134	173	190	219	270	332	403	448	513	538	593	637	720 760	770 820	815 870	870 930	980 1040
B	70	80	90	115	140	170	225	280	323	358	435	485	530	630	630	730	780	830	900
C	60	67	73	73	83	98	127	146	181	184	191	203	219	222	222	280	305	356	368
D	45	52	68	90	110	135	186	240	275	295	360	400	450	550	550	650	700	750	850
Weight (Kg)	3	5	7	9	14	16	26	48	78	90	120	182	202	255	324				

Specification is subject to change without prior notice