


MODEL : RFJ-202 [Rubber Flexible Joint Double Bellows]

Connection : Flange JIS 10K



VTV VALVE, serving Multi-National end users in a wide range of applications in many industries including:

1. Palm Oil and Refinery Plant
2. Petrochemical
3. Power Plant
4. Oil Industries
5. Pulp and Papper Mill
6. Heating
7. Cooling System

- ◆ **Suitable for :** 1. Water
- 2. Steam
- 3. Oil
- 4. Non-abrasive media

Max. Pressure : 10 Bar
Max. Temp : 80°C

◆ DIMENSIONS (mm)

DN		L (mm)	Axial Displacement (mm)		Horizontal Displacement (mm)	Angular Deflection (a1+a2)°	Weight (Kg)
mm	Inch		Extension	Compression			
50	2	150	10	20	20	30°	5
65	2-1/2	150	10	20	20	30°	6
80	3	150	10	20	20	30°	7
100	4	200	15	25	25	30°	10
125	5	200	15	25	25	30°	12
150	6	200	15	25	25	30°	14
200	8	200	20	30	30	30°	20
250	10	200	20	30	30	30°	29
300	12	200	20	30	30	30°	43
350	14	220	20	30	30	30°	61
400	16	220	20	30	30	30°	79
450	18	220	25	30	30	30°	85
500	20	240	25	30	30	30°	94

Specification is subject to change without prior notice